

Spectrum Series 20 High Performance CCC Processor



* Optional touch screen technology

Benefits of Spectrum 20 HPCCC for target compound separation

- Ease and cost of scale-up
- Extremely low solvent usage
- Improved handling of sample solubility issues
- High mass and volume injection loadings
- Total sample recovery
- Reduced sample preparation
- New elution strategies

Typical HPCCC applications in medicinal chemistry

- Solubility: Where solubility of your sample is problematic to your existing purification techniques.
- Product Development: Where you do not want to redevelop your purification processes at each differing scale.
- Purifying Target Compounds: Where you want to purify target compound from crude samples, which are early in their chemistry development and can not be handled by other techniques without significant sample preparation.

Dynamic Extractions specialises in offering separation and purification technology, which provides additional capability to chemists who want to purify products from Discovery stage through Research & Development to Manufacture.

The Spectrum Series 20 High Performance CCC (HPCCC) processor is based on traditional liquid/liquid partitioning and extends the purification options available to chemists in Discovery and Development, who are looking to purify samples from mgs to 5-10 grams of material.

The processor can be provided as a fully operational system or it can be interfaced into existing LC systems to enhance their resolution capability.

The added advantage of the technique is that it easily scales to preparative and kilo scale with no requirement to redevelop the separation method as it is directly transferable from analytical to kilo scale.

The equipment is fully supported by the Dynamic Extractions after sales team that provides: training, feasibility studies, method development and troubleshooting advice. This ensures that all customers have peace of mind and confidence in the technique.

Technical Description

The Dynamic Extractions Spectrum Series 20 is simple in concept and consists of a length of tubing wound in a coil on a drum, which is centrifugally rotated in a planetary motion. Separations are achieved by partitioning the sample between two immiscible liquids: a stationary phase which is retained in the tubing, and a mobile phase which is pumped through the tubing.



The operational process is extremely straightforward. The mixture is introduced in the mobile phase and is separated into its component fractions by the time it emerges at the other end of the tubing. A separation of the mixture occurs, because along the tubing's length there are alternate mixing and settling zones created by the centrifugal forces generated. The order in which the fractions appear depends on how they distribute between the two liquids. The entire sample is recoverable, and highly pure fractions can be obtained since the sample undergoes up to 100,000 mixing and settling steps per hour. This allows the technology to be applied to the separation of substances, which are difficult to purify and/or may be unstable by other existing techniques.

Standard Features

- Column - Scouting - 22ml
- Semi preparative - 136ml
- Performance - 240g (1,600rpm) equipment allowing separations in minutes
- Ease of use - Simple interchange of coils allowing differing separation needs to be met quickly
- Temperature control - Ensures reproducible chemistry of separation
- Safety features
 - Column door interlock
 - Automatic shutdown on out of balance operation
 - Automatic shutdown on high temperature operation
- Low solvent usage - Typically 10% of that used in an equivalent solid phase separation
- Low pressure operation - 60 - 105psi (4-7bar)
- Easy to use - simply interfaced to existing LC equipment (pumps, detector and fraction collector etc)

Technical Specifications

Column Volume (nominal)	22ml	136ml
Sample Load per Injection	10-300mg	1.0-2.0g
Column Bore (id)	0.8mm	1.6mm
Flow Rate (max)	2ml/min	10ml/min



Dimensions

Height	465mm	18 1/2"
Width	535mm	21"
Depth	482mm	19"
Weight	70kg	155lb
Rotor Radius	85mm	3.35"
Electrical Supply	230-115V/50-60Hz	
Power Rating	0.75kVA	



Solving Scale-up and Purification Challenges in Target Compound Separation



Dynamic Extractions Limited
HPCCC instrumentation, Science & Solutions

HRMalytic +61(0)3 9762 2034
ECHnology Pty Ltd

Australian Distributors
Importers & Manufacturers
www.chromtech.net.au

Website NEW : www.chromalytic.net.au E-mail : info@chromtech.net.au Tel: 03 9762 2034 . . . in AUSTRALIA