Trident Integral Guard Cartridge System

Restek's Exclusive Trident Integral System

guard cartridges (page 339).

- Convenient and economical leak-free guard cartridge system, extremely easy to install.
- Versatile configuration protects against all levels of contamination.
- Integral design eliminates troublesome tubing connections.

The system's foundation consists of the analytical column configured with our exclusive Trident end fitting and XF fitting. This configuration contains the standard internal frit as well as a replaceable cap frit, which easily can be changed without disturbing the packed bed. Changing the external frit can reverse the effects of accumulated particles, such as high backpressure or peak distortion. To obtain this basic configuration, simply order any Restek HPLC column, and add the suffix -700 to the catalog number for the column. Nominal additional charge.



Lori McGarry

For maximum protection against contaminants and particulate matter, the system can be configured with an integral guard cartridge holder (XG-XF), a guard cartridge, and a replaceable external frit. To obtain this configuration, simply order any Restek HPLC column, add the suffix -700 to the catalog number for the column, and order the appropriate XG-XF male fitting (cat.# 25026 or 25062, below) and Trident

Description	qty.	cat.#	
XG-XF Fitting for 10mm Guard Cartridge	ea.	25026	
XG-XF Fitting for 20mm Guard Cartridge	ea.	25062	
Replacement XF Filter Fitting	ea.	25024	
Replacement Cap Frits: 4mm, 2.0µm	5-pk.	25022	
Replacement Cap Frits: 4mm, 0.5µm	5-pk.	25023	
Replacement Cap Frits: 2mm, 2.0µm	5-pk.	25057	

Trident Integral Guard System



Assembled column with Trident integral guard system



Column with Trident Integral Inlet Fitting (to order add "-700" to catalog number of column) and guard cartridge, XG-XF fitting, cap frit, and XF end fitting.



Remove the XF end fitting and install the guard cartridge in the end of the column.



Add the XG-XF fitting (order cat.# 25026 for 10mm guard cartidges, cat.# 25062 for 20mm guard cartridges).



Re-install the XF end fitting with cap frit.



The cap frit can be easily replaced if it becomes contaminated/plugged.



