


it's a fact

5 mm Uniliner® liners fit into the 1/4-inch Uniliner® Liner Adaptor, which fits into a 1/4-inch injection port. The Uniliner® liner can be inserted in one direction for direct injections or inverted for on-column injections. Because the 1/4-inch injection port ferrule seals against the metal liner adaptor surface, it is virtually impossible to crack the glass Uniliner® liner during installation.





also **available**

Looking for other packed column accessories for **Agilent GCs?**

See page 232.

Uniliner® Liner

for 1/4-Inch Packed Injection Port Conversion

- Reduces solvent tailing.
- Versatile—0.53 mm ID version can be used in the direct (DI) or on-column (OC) injection mode.
- · Incorporates a gentle taper that seals the column and reduces dead volume in direct injection mode.
- · Available in various designs.

On-column injections can be performed only with 0.53 mm ID columns because 26-gauge needles do not fit into the bore of 0.32 mm ID columns, or into the Unliner® liner taper.

Description	Column ID Injection Mode*	ea. cat.#/price	5-pk. cat.#/price
Uniliner Liner (small buffer volume chamber 60mm long, for injections ≤2μL)	0.53mm DI or OC	20902	20903
Uniliner Liner (large buffer volume chamber 85mm long, for injections ≤4µL)	0.32 & 0.53mm DI only	20308	20309
	0.53mm DI or OC	20301	20305
Cyclo-Uniliner Liner (for active, dirty samples)	0.32 & 0.53mm DI only	20319	20320
Open-Top Uniliner Liner (packed with wool)	0.32 & 0.53mm DI only	20315	20316
Low Volume/Purge & Trap Uniliner Liner (1mm ID x 5mm OD: use in 1/4" injection ports to troubleshoot purge & trap units)	0.32 & 0.53mm DI only	20307	20314
Uniliner Liner Adaptor	Includes 1/+inch nut & graphite ferrule, 1/1s-inch nu and 0.8mm ID graphite ferrule.		
(required for installing Uniliner liners in 1/4" injection ports)		Stainless Steel	Siltek-Treated

	Jp				
rts)	Stainless Steel	Siltek-Treated		
	For injection ports <8cm	20310	22282		
	For injection ports 8-15cm	20311			
	cat.# 20234 (5-pk.)				

1/4" Ferrules for Uniliner Liner Adaptor

*DI = direct injection, OC = on-column injection

Note: a Uniliner liner must be used with a Uniliner Liner Adaptor (cat.# 20310 or 20311) for 1/4-inch injection ports. Remember to include a liner adaptor when ordering a Uniliner liner, unless you are purchasing replacement Uniliner liners.



Website: www.chromtech.net.au E-mail: info@chromtech.net.au TelNo: 03 9762 2034 . . . in AUSTRALIA



