LOW PRESSURE FITTINGS ■ **POLYMERIC**

1/4-28 **PEEK unions**

SPECS

- For 1/16" and 1/8" OD tubing
- Materials Body: PEEK Nut: PPS Ferrules: ETFE
- 1/4-28 threads
- Pressure rating: 1/16" 105 1500 35 500 (Varies with tubing material and ID)



- For easy connection of low pressure solvent lines
- Low dead volume
- For 1/16" or 1/8" OD tubing
- Flat-bottomed 1/4-28 fitting details
- Completely inert and biocompatible

These unions facilitate the quick and reliable connection of two pieces of 1/16" or 1/8" OD tubing. Use with colorcoded adapters for easy solvent line identification.


These are available as the body only, or complete with fittings.

A union with fittings includes:

- PEEK low pressure union
- 2 PPS flangeless hex-head nuts
- ETFE inverted ferrules
- Color-Sleeve adapters

	Bore (mm)	Tubing OD	Qty/pkg	Product No.
Union,	0.50	1/16"	1	JR-1064
with fittings	0.75	1/8"	1	JR-1068
-	1.30	1/8"	1	JR-1065
Body only	0.50	1/16"	1	JR-064
	0.75	1/8"	1	JR-068 ^{9.4} r
	1.30	1/8"	1	JR-065
Spare parts		Tubing OD	Qty/pkg	Product No.
PPS flangeless nuts		1/16"	10	JR-55070-10
		1/8"	10	JR-55071-10
Inverted ETFE ferrules		1/16"	10	JR-041-10
		1/8"	10	JR-051-10





PEEK bulkhead unions

■ For 1/16" and 1/8" OD tubing

SPECS

- Materials Body: PEEK PPS Ferrules: ETFE
- 1/4-28 threads
- Pressure rating: Bar Psi 1/16" 105 1500 1/8" 35 500 (Varies with tubing material and ID)
- Panel mounting (10 mm hole required, max 9 mm thick)
- For easy connection of low pressure solvent lines
- Low dead volume
- For 1/16" or 1/8" OD tubing
- Completely inert and biocompatible

Bulkhead unions are designed to be mounted through an instrument panel or on a bracket.

They are sold complete with fittings, and include:

- 2 PPS flangeless hex-head nuts
- 2 ETFE inverted ferrules
- 2 Color-Sleeve adapters




1/4-28



	Bore (mm,	Tubing OD	Qty/pkg	Product No.
Bulkhead union with fittings	, 0.75 1.50	1/16" 1/8"	1 1	JR-CBUMPK JR-CBULPK
Spare parts		Tubing OD	Qty/pkg	Product No.
PPS flangeless nuts		1/16"	10	JR-55070-10
		1/8"	10	JR-55071-10
Inverted ETFE ferrules		1/16"	10	JR-041-10
		1/8"	10	JR-051-10

TECH TIP

While our PEEK unions are typically used with inverted ferrules, collapsible ferrules or flanged connections can also be used.



ferrule **TECH TIP**

Use our impermeable tubing to avoid gas diffusion in the solvent lines13

RELATED PRODUCTS

Color-coded fingertight	
flanged nuts43	
Color-Sleeve adapters,	
in 12 colors 17	
ligh pressure	
PEEK unions 26	
PPS hex-head	
flanged nuts41	